



# Matrix clay and concrete roofing tiles: Compatible roof hooks

Identifying feature	Processing	Notes	Typen	CrossHook 3S/4S CrossHook 3S long	CrossHook 3S+/4S+	CrossHook 2	SingleHook 1.1	SingleHook Alpin <small>A metal roof plate or sheet metal replacement tile must be placed under the cantilever.</small>	SingleHook Vario	SolidHook SolidHook pantile	SolidHook Vario 1+2	SolidHook plain tiles (Double roofing)	SolidHook plain tiles (Single roofing)	SolidHook slate	
Roof hook types															
				2003215 / 2003144 / 2004222	2002390 / 2002402	2003175	2001928	2003155	2002651	1000001 / 100096 1001508 / 1000653 10000764	1000125 / 1000107	1000214	2003073	1000373	
Rail system															
 <b>Clay roof tiles</b> <ul style="list-style-type: none"> <li>Always 2 watercourses (left + top)</li> <li>Rounded front edge, sharp-edged</li> <li>Distance between battens very different and variable</li> </ul>	<p><b>Processing</b> of the bricks at the lower and upper edge is always necessary.</p>	<p>Large overlap of the tiles possible, therefore note the boom length (T) of the roof hook; see pitched roof brochure "Overview of roof fastenings".</p>		●	●	○	●	●	●	●	●	○	○	○	○
 <b>Concrete roof tile</b> <ul style="list-style-type: none"> <li>Only a lateral watercourse</li> <li>Visible concrete structure on the front side</li> <li>Usually approx. 30 cm wide and approx. 42 cm long</li> <li>L<sub>b</sub> = Distance between battens approx. 31.5 - 34.5 cm</li> </ul>	<p><b>Processing</b> of the bricks at the lower edge is always necessary. - except when using the CrossHook 2 on flat concrete block</p>			○	○	●	○	○	●	●	●	○	○	○	○
 				●	●	○	●	●	●	●	●	○	○	○	○
 <b>Plain tiles</b> <ul style="list-style-type: none"> <li>Scaled optics</li> <li>Same dimensions (approx. 18 x 38 cm)</li> </ul>		Distance between battens: approx. 15 - 17 cm		○	○	○	○	○	○	○	○	●	●	○	○